

### City Life 3/8" x 5 3/4" platform



#### Product Technical Specifications

<b>Nature of material</b>	Top layer: 0,6 mm hardwood Reverse layer: Radiata Pine Substrate: High-density fiberboard (HDF) 900 kg/m <sup>3</sup>
<b>Dimensions</b>	Thickness: 3/8" (10 mm) Width: 5 3/4" (145 mm) Length: 85,83" (2 180 mm). May contain 10% of varying lengths boards.
<b>Profiling</b>	Micro v-joint on 4 sides
<b>Moisture content</b>	Between 6% and 9%
<b>Species and Janka hardness (lb)</b>	Hard Maple (1 450), American Walnut (1 010)
<b>Available grade</b>	Premium: Even appearance. Small character marks without openings are accepted.
<b>Mechanical locking system</b>	Valingue 2G <sup>MD</sup>
<b>Accessories</b>	T-Moldings, Quarter Rounds, Touch-up kits, Maintenance kit



**Mercier Generations Finish:** Acrylate polymer-based finish consisting of plant-based oil and UV-cured polymer and reinforced with suspended aluminum oxide particles.

**Available glosses:** Matte and Matte-brushed (10°), according to the wood species.


**Warranties:**  
20 years for normal residential use  
Limited structural lifetime warranty

**Non-yellowing:** The non-yellowing formula in the finish reduces the natural wood board yellowing process.

**Antimicrobial:** The antimicrobial contained in our finishes helps reduce the risk of spreading bacteria and mildew. Completely non-toxic, this special treatment adds an additional level of protection for healthier floors.

Packaging	Number of boxes	Content	Width	Length	Height	Weight
Box		27,2 sq. ft. (2,5 m <sup>2</sup> )	7"	87"	3"	52 lb (23,1 kg)
Pallet	60	1 632 sq. ft. (151,6 m <sup>2</sup> )	45"	87"	42"	3 200 lb ( 1 361 to 1 451 kg)


#### Colors



Hard Maple  
Belvedere



Hard Maple  
Boulevard



Hard Maple  
Coastline



Hard Maple  
Museum



Hard Maple  
Traffic



American Walnut  
District

## City Life 3/8" x 5 3/4" platform

### Installation

<b>Type of installation</b>	Floating
<b>Relative humidity</b>	Between 25% and 65%
<b>Subfloors</b>	<ul style="list-style-type: none"> <li>• OSB or 3/4" (19 mm) plywood Joists spaced no more than 19" (48,3 cm) C-C</li> <li>• 5/8" (16 mm) plywood Joists spaced no more than 16" (40,6 cm) C-C</li> <li>• 3/8" (10 mm) concrete slab Elevation gain not exceeding 3/16" (5 mm) over a 10' (3 m) distance</li> </ul>
<b>Installation sites</b>	First floor, ground floor and basement
<b>Radiant heated floor</b>	Yes. Refer to the Technical bulletin #5 for more details.

### VOC / Formaldehyde

**VOC-free and formaldehyde-free finish:** ASTM D-5116

**Greenguard Gold certification:** Applies to all species and colors.

**Phtalate-free finish:** OSHA method 104

EPA TSCA Title VI compliant

#### Maximum Greenguard Gold emission criteria

TVOC	≤ 0,22 mg/m <sup>3</sup>
Formaldehyde	≤ 0,0073 ppm
Total Aldehydes	≤ 0,043 ppm
IVOCs	≤ 1/100 TLV and 1/2 chronic REL

### Applicable standards

<b>Surface burning ASTM-E-84</b>	Class C (varies according to the wood species) Flame Spread Index: 100 to 150 Smoke Development: 75 to 400 according to the wood species
<b>Surface burning CAN/ ULC-S102.2</b>	Flame Spread Index (FSR): 115 Smoke Development (SDC): 125
<b>Abrasion resistant finish (Taber test)</b>	<b>Mercier Generations finish:</b> Nema LD3: 1 000 cycles
<b>Static friction coefficient ASTM D2394</b>	<b>Mercier Generations finish:</b> Matte: 0,68

### Certifications



The information in this document was accurate at the time of publication. Mercier Wood Flooring reserves the right to change the products or products characteristics at any time without notice.