Important notice

MERCIER's mission is to walk consumers through the process of choosing a new floor. In this Grade Guidelines, you'll find all the characteristics of each grade and species of wood in the Mercier product line.



THE • • 1 Original Original

Mercier is the pioneer in manufacturing prefinished wood flooring.

Our goal, which stemmed from a visionary and practical need to eliminate on-site finishing of wood floors, was the springboard to our culture of innovation. Dust from sanding, drying times and emissions in the home are now inconveniences of the past thanks to the bold, creative drive that transformed the industry over four decades ago. It is thanks to this culture of innovation, which permeates throughout everything Mercier does, that we have developed a renowned mastery of wood itself, the science of surface finishing, and wood flooring design. Mercier's relentless pursuit to offer the very best of wood and our uncompromising reverence for it—from its inherent properties, nobility and authenticity—is what has enabled us to carve an enviable legacy that can never be equalled.

There can only be one original. Mercier.

Grade selection

The grade classifies the wood boards based on their APPEARANCE. As each board is unique, we group them according to the color variations and character marks that determine the appearance of your floor.

If you prefer a clean, uniform appearance with little variation and very few character marks, you will most likely opt for the Select & Better grade. If you prefer pronounced color variations, the Authentic grade will definitely be your first choice. If moderate variations are more to your taste, the Distinction grade will be your best option.



Table of contents

Species

Collections

43

Red Oak	11
Select & Better	13
Distinction	15
PRO	17
Authentic	19
Herringbone Collection	89
Hard Maple	23
Select & Better	25
Distinction	27
PRO	29
Authentic	31
Herringbone Collection	90
White Oak	35
Authentic	37
R&Q (rift and quarter sawn)	39
Herringbone Collection	91

Hickory Authentic	2
White A	sh
Distinctio	on
Authentic	2
Yellow E	Birch
Select &	Better
Distinctio	on
Authentic	2
America	n Walnut
Authentio	2

43		
45	Origina Callestian	70
49	Origins Collection	73
51	Design+ Collection	75
53		
57	Naked Collection	77
59	Atmosphere Collection	79
61	-	
63	Elegancia Collection	81
67	Element Collection	83
69		00
	PRO Collection	87
	Herringbone Collection	89
	Hardwood	
	Flooring	
	platforms	92
	Glossary	94
	Types of cuts	95







Grain and color

Red Oak is an open grain, ring-porous species that's characterized by visible, well defined growth rings. Tones range from pinkish beige to reddish brown.

Wood oxidation

Red Oak moderately changes color over time, acquiring a slightly amber hue.

Grades

Select & Better	page 13
Distinction	page 13
PRO	page 12
Authentic	page 19
Herringbone Collection	page 89

Low 🖲 🖲 🔿 🔿 🔿 🔿 High

Janka hardness





Grade Select & Better

Light, even appearance with slight color variations between boards. This grade showcases the sapwood's natural tones, from pinkish beige to light brown. Pronounced contrasts in the same board are not allowed in this grade.



Knots

Splits and checks

Sound pin knots are accepted. Limited in number.

Splits and checks are not accepted.



Streaks

Small mineral streaks are accepted. Limited in number. Length

Random lengths Minimum 12" (305 mm)



Grade Distinction

This grade's rich appearance and moderate contrasts are the result of a balanced selection of the species' natural tones, ranging from pinkish beige to medium brown. Light to moderate variation between boards.



Knots

Small sounds and repaired knots are accepted. Limited in number and diameter.

Splits and checks

Splits are not accepted in this grade. Occasional surface checks are accepted.



Streaks

Small mineral streaks of any length are allowed. Limited in number.

Random lengths

Length

Minimum 12" (305 mm)



Grade



The contrasting appearance of this grade represents a mix of the species' natural full-bodied tones. Moderate variation between boards.



Knots

Sound knots and knots filled with wood putty are accepted without limitation. Openings in and around knots are accepted.

Splits and checks

Length

Occasional surface checks and occasional end splits are accepted in this grade. Random lengths Minimum 12" (305 mm)



Streaks

Mineral streaks are accepted without limitation.

Other characteristics

Occasional sticker stains are accepted.



Grade

Authentic

The contrasting appearance of this grade represents a mix of the species' natural full-bodied tones. Moderate to pronounced variation between boards.

.



Knots

Sound knots and knots filled with wood putty (including slight openings or depressions) are accepted without limitation. Small openings in and around knots are accepted.

Splits and checks

Surface splits and checks and end splits are accepted

Length*

Random lengths Minimum: 6 ¹/₂": 16" (406 mm) 8 ¹/₈": 18" (457 mm)

* May occasionally include 12" (305 mm) boards.



Streaks

Mineral streaks are accepted without limitation.

Other characteristics

Varnish cracks around character marks are accepted.



Atmosphere Collection Hard Maple Hush



Grain and color

Hard Maple has a fine and even-textured grain. Growth rings are narrow and lightly contrasted. Color variations range from the sapwood's whitish beige to a full-bodied brown, making it the lightest-toned hardwood species.

Wood oxidation

Hard Maple undergoes a moderate change in color over time, acquiring a golden hue.

Grades

Select & Better	page 23
Distinction	page 22
PRO	page 29
Authentic	page 31
Herringbone Collection	page 90

Low 🖲 🖲 🔵 🔿 📿 High

Janka hardness





Grade

Select and Better

Light, even appearance, with slight color variations between boards. This grade showcases the sapwood's natural tones, ranging from creamy white to very light brown. Pronounced contrasts within a single board are not allowed in this grade.



Knots

Splits and checks

Sound pin knots are accepted. Limited in number. Splits and checks are not accepted.



Streaks

Small mineral streaks are accepted. Limited in number.

Length

Random lengths Minimum 12" (305 mm)



Grade

Distinction

This grade's rich, moderately contrasted appearance is the result of a balanced selection of the species' natural tones, ranging from creamy white to medium brown. Light to moderate variation between boards.



Knots

Small sound and repaired knots are accepted. Limited in number and diameter.

Splits and checks

Splits are not accepted in this grade. Occasional surface checks are accepted.



Streaks

Small mineral streaks of any length are allowed. Limited in number.

Random lengths Minimum 12" (305 mm)

Length



Grade



The contrasting appearance of this grade represents a mix of the species' natural full-bodied tones. Moderate variation between boards.



Knots

Sound knots and knots filled with wood putty are accepted without limitation. Small openings in and around knots are accepted.

Splits and checks

Occasional surface checks and occasional end splits are accepted in this grade.

Length

Random lengths Minimum 12" (305 mm)



Streaks

Mineral streaks are accepted without limitation.

Other characteristics

Occasional sticker stains are accepted.



Grade

Authentic

This grade is high in contrasts, reflecting the full range of vivid natural tones found in the species. Moderate to pronounced variation between boards.



Knots

Sound knots and knots filled with wood putty (including slight openings or depressions) are accepted without limitation. Openings in and around knots are accepted.

Splits and checks

Surface splits and checks and end splits are accepted in this grade.

Length*

Random lengths Minimum: 6 ¹/₂": 16" (406 mm) 8 ¹/₈": 18" (457 mm)



Streaks

Mineral streaks are accepted without limitation.

Other characteristics

Varnish cracks around character marks are accepted in this grade.

* May include some 12" (305 mm) boards.



Naked Collection White Oak Authentic 6 1/2"



Grain and color

White Oak has an open grain and is ring porous, with visible, well-defined growth rings, similar to Red Oak. The tones range from creamy light beige to greyish brown.

Wood oxidation

White Oak undergoes a moderate change in color over time, acquiring an amber hue.

Grades

Authentic	page 37
R&Q (rift and quarter sawn)	page 39
Herringbone Collection	page 91

Janka hardness





White Oak

Grade

Authentic

This grade's rich, moderately contrasting appearance is the result of a balanced mix of all the species' natural tones, from creamy beige to vivid brown. Moderate variation between boards.



Knots

Sound knots and knots filled with wood putty (including slight openings or depressions) are accepted without limitation. Openings in and around knots are accepted.

Splits and checks

Surface splits and checks and end splits are accepted in this grade.

Length*

Random lengths Minimum: 2 ¹/₄", 3 ¹/₄", 4 ¹/₄" and 5": 12" (305 mm) 6 ¹/₂": 16" (406 mm) 8 ¹/₈": 18" (457 mm)



Streaks

Mineral streaks are accepted without limitation.

Other characteristics

For 6 $\frac{1}{2}$ " and 8 $\frac{1}{8}$ " boards only: varnish cracks around character marks are accepted in this grade. * May include some 12" (305 mm) boards.



White Oak

$\underline{\mathbf{Grade}} \quad \mathbf{R\&Q} \ (\mathbf{rift} \ \mathbf{and} \ \mathbf{quarter} \ \mathbf{sawn})$

Uniform and with moderate contrasts, the R&Q grade features a linear single grain, which is distinctive to quarter sawn wood. The coloration is a balanced blend, ranging from cream to golden brown, Light to moderate variation between boards.



Knots _____

Sound knots and knots repaired with wood putty are accepted in limited amounts. Limited in number.

Splits and checks

Splits are not accepted in this grade. Occasional surface checks are accepted.



Streaks

Mineral streaks of any length are allowed.

Random lengths

Length*

Minimum 16" (406 mm)

* May occasionally include some 12" (305 mm) boards.



Hickory





Grain and color

Hickory is a dense, closed-grain wood with visible growth rings. Its color is characterized by a wide range of tones and variations, from golden beige to an intense blackish brown. Prominent character marks give it a rustic, natural look.

Wood oxidation

Hickory undergoes a slight change in color over time, acquiring a golden hue.





Hickory

Grade

Authentic

This grade is high in tonal contrasts, showcasing the full range of vivid natural colors found in the species. Pronounced variation between boards.



Knots

Sound knots and knots filled with wood putty (including slight openings or depressions) are accepted without limitation. Openings in and around knots are accepted.

Splits and checks

Surface splits and checks and end splits are accepted in this grade.

Length*

Random lengths Minimum: $2 \frac{1}{4}^{"}$, $3 \frac{1}{4}^{"}$, $4 \frac{1}{4}^{"}$ and $5^{"}$: 12" (305 mm) $6 \frac{1}{2}^{"}$: 16" (406 mm)

* May include some 12" (305 mm) boards.



Streaks

Other characteristics

Mineral streaks are accepted without limitation.

Varnish cracks around character marks are accepted in this grade.







Grain and color

White Ash is ring porous, with visible, well-defined growth rings. Its rich spectrum of colors ranges from creamy white with golden undertones to an intense dark brown.

Wood oxidation

Ash undergoes a moderate change in color over time, acquiring an amber hue.





White Ash

Grade Distinction

This grade's rich, high-contrast appearance showcases the species' full range of natural tones, from creamy white to dark brown. Moderate to pronounced variation between boards.



Knots

Sounds and repaired knots are accepted. Limited in number and diameter.

Splits and checks

Splits are not accepted in this grade. Occasional surface checks are accepted.



Streaks

Small mineral streaks of any length are allowed. Limited in number.

Random lengths Minimum 12" (305 mm)

Length



White Ash

Grade

Authentic

The rich and contrasting appearance of this grade represents a mix of the species' natural full-bodied tones, ranging from creamy white to dark brown. Moderate to pronounced variation between boards.

grade.



Knots

Sound knots and knots filled with wood putty (including slight openings or depressions) are accepted without limitation. Openings in and around knots are accepted.

Splits and checks

Surface splits and checks and

end splits are accepted in this

Length

Random lengths Minimum 16" (406 mm)



Streaks

Mineral streaks are accepted without limitation.

Other characteristics

Varnish cracks around character marks are accepted in this grade.



Collection Elegancia Yellow Birch Authentic 3 1/4" Palomino

THEFT



Grain and color

Yellow Birch is straight grained and even textured, with fine, lightly contrasting growth rings. Colors range from the creamy, sometimes pinkish white of the sapwood to an intense reddish brown.

Wood oxidation

Yellow Birch undergoes a moderate change in color over time, acquiring a slightly amber hue.

Low 🖲 🖲 🔿 🔿 🔿 High

Janka hardness



Grades

Select & Better	page 52
Distinction	page 59
Authentic	page 6



Yellow Birch

Grade Select & Better

Clear and even in appearance, with slight to moderate color variation between boards. This grade showcases the sapwood's natural tones, ranging from creamy beige to a pink-tinged light brown. Pronounced contrasts within a single board are not allowed in this grade.



Knots

Splits and checks

Sound pin knots are accepted. Limited in number. Splits and checks are not accepted.

Length



Streaks

Small mineral streaks are accepted. Limited in number.

Minimum 12" (305 mm)



Yellow Birch

Grade Distinction

This grade's rich, high-contrast appearance showcases the species' full range of natural tones, from creamy beige to reddish brown. Moderate to pronounced variation between boards.



Knots _____

Small sound knots and repaired knots are accepted. Limited in number and diameter.

Splits and checks

Splits are not accepted in this grade. Occasional surface checks are accepted.



Streaks

Small mineral streaks of any length are allowed. Limited in number.

Random lengths Minimum 12" (305 mm)

Length



Yellow Birch

Grade

Authentic

This grade is high in contrasts, reflecting the full range of the species' natural, full-bodied tones. Pronounced variation between boards.

grade.



Knots

Sound knots and knots filled with wood putty (including slight openings or depressions) are accepted without limitation. Openings in and around knots are accepted.

Splits and checks

Length

Surface splits and checks and end splits are accepted in this Random lengths Minimum: 12" (305 mm)



Streaks

Mineral streaks are accepted without limitation.

Other characteristics

Varnish cracks around character marks are accepted in this grade.

American Walnut

Origins Collection American Walnut Authentic 6 1/2" Natural

• • • • • •



American Walnut

Latin name : Juglans nigra

Grain and color

American Walnut has a fine, straight grain. It's characterized by uncommonly deep, rich colors ranging from beige to almost white in the sapwood and light to chocolate brown in the heartwood.

Wood oxidation

Walnut undergoes a moderate change in color over time, turning a lighter, more even golden brown.

Grade
Authentic page 67





Janka hardness





American Walnut

Grade

Authentic

This grade's rich appearance and moderate contrasts reflect the species' wide range of natural colors, from the beige of the sapwood to chocolate brown. Pronounced variation between boards.



Knots

Sound knots and knots filled with wood putty (including slight openings or depressions) are accepted without limitation. Openings in and around knots are accepted.

Splits and checks

Surface splits and checks and end splits are accepted in this grade. Splits filled with wood putty are accepted.

Length*

Random lengths Minimum: 16" (406 mm)

* May occasionally include some 12" (305 mm) boards.



Streaks

Mineral streaks are accepted without limitation.

Other characteristics

Varnish cracks around character marks are accepted in this grade. The beige coloration of the sapwood is allowed without limitation.

Atmosphere Collection Hickory Authentic 6 1/2" Hush

Introduction of the collections

Each of our collection has its own personality. Browse our collections to find the floor that suits your lifestyle.



Origins Collection White Oak Authentic 6 1/2" Natural



Pure and natural

A selection of North American species. Stain-free, natural wood.

Grades

For a detailed description of grades, please refer to the list opposite.

Red Oak		Hickory	
Red Oak Select & Better	page 13	Hickory Authentic	page 45
Red Oak Distinction	page 15	Yellow Birch	
Red Oak Authentic	page 19		
		Yellow Birch Select & Better	page 57
Hard Maple		Yellow Birch Distinction	page 59
Hard Maple Select & Better	page 25	Yellow Birch Authentic	page 61
Hard Maple Distinction	page 27		
Hard Maple Authentic	page 31	American Walnut	
		American Walnut Authentic	page 65
White Oak			
White Oak Authentic	page 37		
White Oak R&Q	page 39		


10101



Customized flooring never looked this good

A floor created especially for you among a selection of the finest colors offered on Hard Maple and Red Oak. Choose the species, the grade, the color, the finish, the gloss, and board width.

Grades

For a detailed description of grades, please refer to the list opposite.

Red Oak		Hard Maple	
Red Oak Select & Better	page 13	Hard Maple Select & Better	page 25
Red Oak Distinction	page 15	Hard Maple Distinction	page 27
Red Oak Authentic	page 19	Hard Maple Authentic	page 31





The true color of wood

Thanks to Mercier unique finishing process, the original color of raw wood is sealed and kept in its simplest expression.

Color oxidation

The effect of oxidation on the boards is very slight, producing a more saturated version of the original tone.

Grades

For a detailed description of grades, please refer to the list opposite.

White Oak		Hickory	
White Oak Authentic	page 37	Hickory Authentic	page 45
White Oak R&Q	page 39	American Walnut	
Hard Maple		American Walnut Authentic	page 65
Hard Maple Distinction	page 27		
Hard Maple Authentic	page 31		



Atmosphere COLLECTION

Organic beauty in transparency

Atmosphere's light neutral shades blend with natural highlights to showcase wood's awe-inspiring texture and grain.

Color oxidation

The effect of oxidation on the boards is very slight, producing a more saturated version of the original tone.

Grades

For a detailed description of grades, please refer to the list opposite.

Red Oak		White Oak	
Red Oak Distinction	page 15	White Oak Authentic	page 37
Red Oak Authentic	page 19	White Oak R&Q	page 39
Hard Maple		Hickory	
Hard Maple Distinction	page 27	Hickory Authentic	page 45
Hard Maple Authentic	page 31		





Refined innovation

With its stylish colors and looks, Elegancia pays tribute to the nobility and beauty of wood.

Grades	White Ash		Hickory	
	White Ash Distinction	page 51	Hickory Authentic	page 45
For a detailed description of grades, please refer to the list opposite.	White Oak		Yellow Birch	
	White Oak Authentic	page 37	Yellow Birch Distinction	page 59
	White Oak R&Q	page 39	Yellow Birch Authentic	page 61

Element Collection White Oak Authentic 5"

Element COLLECTION Rich and reactive contrasting nuances

Element stuns with color variations that make each board unique thanks to a process that reacts with the tannins in the wood.

Color oxidation

The color change is pronounced for Yellow Birch and Hard Maple and is moderate for American Walnut, white oak and Hickory. The color takes on a more golden, and saturated tone.

Grades	White Oak		Hickory	
	White Oak Authentic	page 37	Hickory Authentic	page 45
For a detailed description of grades, please refer to the list opposite.	Hard Maple		American Walnut	
	Hard Maple Distinction	page 27	American Walnut Authentic	page 65
	Hard Maple Authentic	page 31		

Element COLLECTION









Affordable and timeless

An affordable collection of timeless colored Hard Maple and Red Oak floors.

	Red Oak	
Grade	Red Oak PRO	page 17
For a detailed description of the grade, please refer to the list opposite.	Hard Maple	
	Hard Maple PRO	page 29



Herringbone

Timeless herringbone pattern

A timeless classic with panache, Herringbone pattern brings a graphical touch and depth to any space.

Red Oak

Colors

Refer to the product chart for the complete product availability.



Grade

Knots

Small sounds and repaired knots are accepted. Limited in number and diameter.

Distinction

Splits and checks

Splits are not accepted in this grade. Occasional surface checks are accepted.





Streaks

Small mineral streaks of any length are allowed. Limited in number.



Timeless herringbone pattern

A timeless classic with panache, Herringbone pattern brings a graphical touch and depth to any space.

Hard Maple

Colors

Grade

Distinction

Refer to the product chart for the complete product availability.



Knots

Small sounds and repaired knots are accepted. Limited in number and diameter.

Splits and checks

Splits are not accepted in this grade. Occasional surface checks are accepted.



Streaks

Small mineral streaks of any length are allowed. Limited in number.



Herringbone

Timeless herringbone pattern

A timeless classic with panache, Herringbone pattern brings a graphical touch and depth to any space.

White Oak

Colors

Grade

Distinction

Refer to the product chart for the complete product availability.



Knots

Small sounds and repaired knots are accepted. Limited in number and diameter.

Splits and checks

Splits are not accepted in this grade. Occasional surface checks are accepted.





Streaks

Small mineral streaks of any length are allowed. Limited in number.

Hardwood floor platforms

	SOLID	ENGINEERED (Engineered wood)
	(Solid wood)	1/2"	3/4"
NATURE OF MATERIAL	100% Hardwood	Top layer: Hardwood, 4 mn Base: Hardwood plywood	n thick
TYPES OF INSTALLATION	Nailed and stapled	Nailed, glued, stapled* and floating**	Nailed, glued, stapled* and floating**
INSTALLATION IN THE BASEMENT OR ON CONCRETE	Not recommended	Possible	Possible
SANDING	Yes: 3 to 5 times	Yes: 3 to 5 times	Yes: 3 to 5 times
SPECIES	Hard Maple Hickory Red Oak White Ash White Oak Yellow Birch	American Walnut Hard Maple Hickory Red Oak White Oak	American Walnut Hard Maple Hickory Red Oak White Oak

* Refer to Technical Bulletin # 9

** Excluding Hickory and the 8 1/8" (206 mm) width

	SOLID	ENGINEERED (I	Engineered wood)
	(Solid wood)	1/2"	3/4"
GRADES (ACCORDING TO THE SPECIES)	Select & Better Distinction Authentic PRO	Select & Better Distinction Authentic R&Q	Distinction Authentic R&Q
THICKNESS AND WIDTH (ACCORDING TO THE SPECIES)	2 ¼" (57 mm) x ¾" (19 mm) 3 ¼" (83 mm) x ¾" (19 mm) 4 ¼" (108 mm) x ¾" (19 mm)	3 ¼" (83 mm) x ½" (12,7 mm) 5" (127 mm) x ½" (12,7 mm) 6 ½" (165 mm) x ½" (12,7 mm)	5" (127 mm) x ¾" (19 mm) 6 ½" (165 mm) x ¾" (19 mm) 8 ⅛" (206 mm) x ¾" (19 mm)
LENGTHS	Random	Random	
HERRINGBONE AVAILABILITY (Suitable for Herringbone pattern installation only)	Not available	Refer to the Product Chart for the availability of the product Hard Maple Red Oak White Oak 5" (127 mm) X ½" (12,7 mm) Length: 18" (45,7 cm)	Not available

Glossary & characteristics

1 Sapwood: The part of the tree located near the outside of the trunk, between the heartwood (duramen) and the bark. It is usually of a lighter color than the heartwood.

darker than the sapwood.

3 Hardwood: Generally, one of the botanical groups of deciduous trees that have broad leaves in contrast to the conifers of softwoods. The terms have no reference of the flooring strips when they are laid side by side. The result is a small "V" to the actual hardness of the wood.

4 Annual growth ring: The layer of wood growth, including spring and summerwood, formed on a tree during a single growing season

5 Janka hardness: A hardness test measuring the force required to drive a 0.444" (11.3 mm) steel bearing half its depth into the wood. The more force required, the harder the wood. Red Oak is the industry benchmark for comparing the relative hardness of different wood species.

6 Split: A lengthwise separation of fibres resulting from natural, environmental and/or mechanical pressures. May be at the end of a board or on the surface.

7 Check: A short, narrow, shallow separation of the wood, perpendicular to the annual growth rings. May be located in the centre or at the ends of boards.

8 Grade: The classification of flooring strips based on the natural color and character marks in the wood (mineral streaks, knots, etc.). The grade refers to the appearance of the product.

9 Relative humidity: The ratio of the amount of water vapour present in the air to the amount of water that can be held by that air at a given temperature.

10 Gloss: The gloss level or luster of a surface is determined by the amount of light it reflects. A glossy surface reflects more light than a matte surface.

11 Character marks: Natural "imperfections" in the wood such as mineral streaks, knots and coloration that give the product its unique appearance.

12 Wood oxidation: A natural phenomenon by which the color of wood changes **2 Heartwood:** The part of the tree between the pith and the sapwood. It is usually after exposure to air and ambient light. This change varies depending on the species.

> **13 Micro V-joint:** The 45° angle at the junction between the surface and the side shape, whence the name "V-joint."

14 Pith: The soft-surfaced core of a tree trunk or branch.

15 Knot: The portion of a branch embedded in the wood. There are several types of knots, including sound and open knots.

16 Pin knot: A tiny sound knot, less than 1/8" (3.2 mm) in diameter.

17 Open knot: A knot that is open in the centre; it is often filled with wood putty.

18 Engineered wood flooring: A floor made up of a hardwood surface bonded to a substrate.

19 Rays: The cellular structure of the tree extending from the outer part of the tree toward the centre (perpendicular to the annual growth rings).

20 Mineral streak: A general term describing a pigmentation in the wood. This coloration appears in the form of a streak or stain ranging from greenish brown to jet black.

Types of cuts









Flat sawn:

The most common sawing method. It results in a wide variety of colors, with straight and curved patterns, so that each board sawn this way has a unique appearance.



Quarter and rift sawn:

A sawing method in which the annual growth rings form a 45° or 90° angle with the surface of the board. This creates a straightline pattern along the length of the board. When the angle is close to 90°, the result is the wavy perpendicular patterns characteristic of R&Q (rift and quarter sawn) boards.

Naked Collection American Walnut Authentic 6 1/2"

A STAR

1

8, Rue de Cherche-